

INDUSTRIAL | 7.5 HP ROTARY SCROLL AIR COMPRESSORS

Gardner Denver EnviroAire compressors provide the reliable, high quality compressed air that you've come to expect from Gardner Denver. EnviroAire compressors offer a wide selection of configurations and top-quality available options. Gardner Denver designed this series specifically for industrial and laboratory applications that require 100% oil-less air. Experience proven results with Gardner Denver-the leader in durability, reliability and efficiency.

Standard Equipment

- Continuous operation, 100% duty cycle
- 5 Micron industrial grade intake air filter
- ASME coded receiver
- Premium efficient TEFC motor
- Unique tip seal design
- Low sound levels and vibration
- Re-greasable bearings
- Integral cooling fan
- Easy accessibility for maintenance
- 1-Year package warranty
- 1-Year airend warranty

Available Options

- Tank Sizes—30, 80, 120 or 240 gallon
 - Galvanized receiver
 - Vinyl (epoxy) lined receiver
- Electronic tank drain
- Mass. code fittings
- Starter
- High temp switch
- Vibration isolators
- Dryer options
 - Refrigerated dryer
 - Desiccant dryer



BARE AIREND

MODEL	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS		
SC7	16.3 × 16.1 × 13.9	61		

SIMPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.		IDENTIFICATION	DIMENSIONS	APPROX.	116 PSI RATING		140 PSI RATING	
	NUMBER	L × W × H IN.	SHIP WEIGHT LBS	RPM	ACFM	RPM	ACFM	
7.5	Base	BENVS7	38 × 21 × 17	375	3340	22.1	2650	16
7.5	30	HENVS7-3	43 × 24 × 38	625	3340	22.1	2650	16
7.5	80	HENVS7-8	67 × 24 × 42	750	3340	22.1	2650	16
7.5	120	HENVS7-12	71 × 27 × 46	850	3340	22.1	2650	16

DUPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.		IDENTIFICATION		APPROX. SHIP WEIGHT	116 PSI RATING		140 PSI RATING	
	NUMBER	IN.	LBS	RPM	ACFM	RPM	ACFM	
7.5	Base	BENVS7D	48 × 22 × 36.5	900	3340	44.2	2650	32
7.5	80	HENVS7D-8	65 × 26 × 61.5	1300	3340	44.2	2650	32
7.5	120	HENVS7D-12	69 × 27 × 65.5	1400	3340	44.2	2650	32
7.5	240	HENVS7D-24	86 × 33 × 71.5	1600	3340	44.2	2650	32

Simplex CFM values are doubled for duplex units. Duplex units have two motors and two pumps on one base/tank.

TRIPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.			DIMENSIONS L × W × H	APPROX.	116 PSI RATING		140 PSI RATING	
	NUMBER	IN.	SHIP WEIGHT LBS	RPM	ACFM	RPM	ACFM	
7.5	Base	BENVS7T	48 × 22 × 54.5	1350	3340	66.3	2650	48

Simplex CFM values are tripled for triplex units. Triplex units have three airends and three motors stacked on a common base.

QUADRAPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.		IDENTIFICATION	DIMENSIONS	APPROX. SHIP WEIGHT	116 PSI RATING		140 PSI RATING	
	NUMBER	L × W × H IN.	LBS	RPM	ACFM	RPM	ACFM	
7.5	Base	BENVS7Q	48 × 22 × 72	2000	3340	88.4	2650	64

Simplex CFM values are quadrupled for Quadraplex units. Quadraplex units have four airends and four motors stacked on a common base.



Gardner Denver, Inc.

1800 Gardner Expressway Quincy, IL 62305 866-440-6241 www.gardnerdenver.com/gdproducts

©2017 Gardner Denver, Inc. Printed in U.S.A. GLCS-ENV-IND-S7 1st Ed. 2/17



Please recycle after use.

